



Data subject to change without prior notice
Edition 12/2025 © 2025 JMG Cranes S.p.A. All rights reserved
Rev. 0/25

EU standards CE

UNI ISO 4301-1: A1

2006/42 CE-2014/30 UE-2014/35 UE
2000/14 CE and subsequent amendments.

EN 13000:2014-ANSI/ASME B30.5-2021
and subsequent amendments.



JMG Cranes S.p.A.

Offices and plant: Via dell'Innovazione, 3 - 29010 Sarmato (PC) - Italy

Registered Office: Via Dante, 15 - 26100 Cremona - Italy

Administration: Via Bergamo, 142 - 26100 Cremona - Italy

+39 0523 8486

info@jmgcranes.com

www.jmgcranes.com

Electric pick & carry cranes

M Series

MC250.08

(metric)

Maximum capacity
50t



JMG®

- **Radio remote controlled crane**
- **Telescopic boom**
- **Front-wheels drive with counter rotation**
- **3 position tiltable head (0°/+40°/+80°)**
- **Extendable rear group up to 1200mm with real time load capacity**
- **5 removable counterweights**

- Changeable and modular booms
- Lithium battery
- Hydraulic winch
- Mechanical jib
- Mechanical extension
- Hydraulic jib with hydraulic extension
- Hydraulic forks with hydraulic positioner
- Hydraulic forks with side shifting
- Customer paint colour

Extended length: 2.850 mm
(from the front of the machine)

Closed length: 350 mm
(from the front of the machine)

Max load hook: 50t

Max load forks: 33t@600mm

Boom weight: 3.350 kg

[illegible]